ADA035806

NPS-01276111

NAVAL POSTGRADUATE SCHOOL
Monterey, California

A SUMMARY OF THE

FOUNDATION RESEARCH PROGRAM

November 1976

Report for the Period

1 July 1975 to 30 June 1976

Approved for public release; distribution unlimited

Prepared for:
Chief of Naval Research
Arlington, Virginia 22217 and
Director of Laboratory Programs
Washington, D. C. 20360

DDC
RECEIVED
FEB 22 1977
A

NAVAL POSTGRADUATE SCHOOL
Monterey, California

Rear Admiral I. W. Linder, USN   Jack R. Borsting
                                                  Provost

Reproduction of all or part of this report is authorized.

This report was prepared by:

Robert R. Fossum
Dean of Research

Released by:

Jack R. Borsting
Provost

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
NPS-01276111		

4. TITLE (and Subtitle)

COMPILATION OF BRIEF SUMMARIES FOR THE FY 1976 FOUNDATION RESEARCH PROGRAM.

5. TYPE OF REPORT & PERIOD COVERED

Summary Report.
1 July 1975 — 30 June 1976.

6. PERFORMING ORG. REPORT NUMBER

7. AUTHOR(s)

Faculty of Naval Postgraduate School

8. CONTRACT OR GRANT NUMBER(s)

9. PERFORMING ORGANIZATION NAME AND ADDRESS

Naval Postgraduate School
Monterey, California 93940

10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS

61152N; RR 000-01-10
N0001476 WR 60052 62766N;
ZF61-512-001 N0003776WR65014

11. CONTROLLING OFFICE NAME AND ADDRESS

Chief of Naval Research, Arlington, Virginia 22217
Director of Laboratory Programs, Washington, D.C. 20360

12. REPORT DATE

November 1976

13. NUMBER OF PAGES

79

14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)

15. SECURITY CLASS. (of this report)

UNCLASSIFIED

15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

This document consists of 43 summaries of

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Foundation Research Program	Finite Element Analysis,	Fatigue Testing,
Equatorial Waves,	Military Health Care,	Transonic Engine Flow,
Air Pollution,	Lasers,	

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

Forty-three summaries of Independent Research/Independent Exploratory Development work carried out under funding to the Naval Postgraduate School Foundation Research Program. This research was carried out in the areas of Computer Science, Mathematics, Administrative Science, Operations Research, Physics & Chemistry, Electrical Engineering, Meteorology, Aeronautics, Oceanography, and Mechanical Engineering. A tabulation in the index identifies area of research and the principal investigator. The category of independent research or independent exploratory research is also identified for each research task.

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE
1 JAN 73
S/N 0102-014-6601

UNCLASSIFIED

Rear Admiral Robert K. Geiger, USN
Chief of Naval Research
Washington, D.C.

Dear Admiral Geiger:

The thirtieth anniversary of the Office of Naval Research
has been celebrated this year with ceremony and praise - and,
more importantly, with thoughtful realization within the sci-
entific community of the immense value of the basic research
fostered and supported by ONR in universities and laboratories
across the nation. The Office of Naval Research has led the way
in the creation of policies for the support of scientific research
and has earned and holds the respect of scholars throughout the
United States.

From its beginning the Office of Naval Research has main-
tained a close and special relationship with the Naval Postgrad-
uate School. The substantial scientific research program which
supports the academic progress of the Postgraduate School today
was inaugurated by ONR support of scholarly investigations by
faculty and officer students. Postgraduate School Technical
Report #1, issued in 1949, presents the results of mathematical
and physical analyses performed in fulfillment of an ONR project.
The Naval Postgraduate School Foundation Research Program
through which ONR today provides support for new and imag-
inative areas of investigation, is the logical evolution of that
initial project.

This close relationship between the Navy's graduate educa-
tion university and the Navy's scientific research organization
extends also to our mutual efforts to maintain close ties with
the scientific community in the universities of our nation. The
Office of Naval Research sponsorship of distinguished scholars
as visiting faculty members at the Postgraduate School broadens
and strengthens these ties.

With so many positive and productive developments in the
30 years of support of science by the Office of Naval Research
the Postgraduate School looks forward with anticipation and
enthusiasm to the future products of our close association.

Sincerely,

ISHAM LINDER
Rear Admiral, U. S. Navy

TABLE OF CONTENTS

1

FY 1976 FOUNDATION RESEARCH

I.   Introduction

The principal thrust of research and exploratory development program at the Naval Postgraduate School (NPS) stems from its mission:

> To conduct and direct advanced education of commissioned officers, and to provide such other technical and professional instruction as may be prescribed to meet the needs of the Naval Service; and in support of the foregoing to foster and encourage a program of research in order to sustain academic excellence.

In fulfillment of the research and development program objectives and within the above constraints, the Naval Postgraduate School

> Initiates and conducts scientific and applied research (6.1) of a long-range nature in areas of special interest to the Navy.

> Conducts exploratory development (6.2) deriving from scientific program areas or in other areas specifically requested by the Navy.

In addition, NPS performs scientific research and exploratory development, where uniquely qualified, for other agencies of the Department of Defense and, in defense related efforts, for other Federal Government agencies. NPS also furnishes consulting services for the Navy and, where specifically qualified, for other agencies of the Department of Defense and in defense related efforts for other Government agencies.

II. Background on the NPS Research Program

The Navy has developed the Naval Postgraduate School as an academic institution which uses university educational methods to address the special graduate education requirements of the Navy. The Superintendent of the Naval Postgraduate School is a Rear Admiral of the line of the Navy. He is supported by a dual management structure, part military and part civilian. The faculty, mostly civilian, is responsible for the academic programs and, in support of these, conducts an active research effort. The military staff specifies the educational needs of the Navy, in terms of curricula, and provides administrative logistic support.

At the Naval Postgraduate School, as in other academic institutions, the faculty is organized into departments. The department represents a resource center of faculty members with allied disciplinary specialization. Currently, the departments at the Naval Postgraduate School include Computer Science, Mathematics, Administrative Science, Operations Research, Physics and Chemistry, Electrical Engineering, Meteorology, Aeronautics, Oceanography, Mechanical Engineering, and National Security Affairs. Inter-disciplinary groups which have effective departmental status include Engineering Acoustics and Anti-Submarine Warfare.

Research and development projects are largely conducted by the individual faculty members on a project basis. Projects typically originate from proposals prepared either by individual faculty members, or by groups of faculty members from the same or different departments.

The research program is divided administratively into two parts. First is the Sponsored Research Program. This program includes projects awarded by sponsoring agencies to an individual principal investigator. The principal source of funds is the various commands and laboratories of the Naval Material Command. The sponsored program constitutes about 80% of the total NPS research program. The Foundation Research Program is based on a grant from the Chief of Naval Research and the Director of Navy Laboratories. This program is administered internally by a Research Council, made up of faculty members appointed by the Provost. The Dean of Research is the Chairman of the Council. The Council meets periodically to review faculty proposals, allocate funding, and review results of completed projects.

Appendix I identifies each project by title and category or type funding (Research - 6.1 and Exploratory Development - 6.2). The 6.1 category was funded by the Chief of Naval Research, Arlington, Virginia 22217 and the 6.2 category was funded by Director of Laboratory Programs, Washington, D. C. 20360.

This report summarizes the FY 1976 Foundation Research Program.

Title: Large Scale Network Optimization

Investigator: Gerald Brown, Associate Professor, Computer Science and Operations Research

Sponsor: Foundation Research Program (6.2)

Objective: To study mathematical methods leading to efficient optimization of large scale pure network cost minimization models.

Summary: An evaluation was made of many methods for pure network optimization with the view of producing extremely fast computer routines and a robust mathematical treatment of the class of problems. Several computer packages were developed for the capacitated transshipment problem and the transportation problem. Test problems as large as 20,000 equations and 50,000 variables have been solved to date with computational times and costs far less than any known competing implementation. Additional routines have been developed for network problems with nonlinear costs, transportation and transshipment problems with relatively few sources and a large number of destinations, and single commodity distribution problems imbedded in large multicommodity models. The improvements in network solution times have been exploited by larger optimization systems using pure network subproblems. The network package GNET has been distributed to many universities and to several federal and Department of Defense agencies. In addition, several hundred information requests have been received for various aspects of the results. Continuing research focuses on still larger problems, with a working goal of 1,000,000 variable models.

Publications: G. Bradley, G. Brown and G. Graves, "GNET, A Primal Network Computer System for Solution of Capacitated Network Flow Problems," copyright 1975.

Conference
Presentations: G. Bradley, G. Brown and G. Graves, "Tailoring
Primal Network Codes to Classes of Problems
with Common Structure," presented at the
Joint National Meeting of ORSA/TIMS, Las
Vegas, November 1975.

G. Bradley, G. Brown and G. Graves, "Surrogate
Programming Approach to Solution of Large
Scale Network Problems," presented at the
Joint National Meeting of ORSA/TIMS, Philadelphia, PA,
March 1976.

Title: Analysis of Binary Trees Arising from Applications
                  in Sorting and Information Retrieval

Investigators: Gerald Brown, Associate Professor, Computer
                  Science and Operations Research, and Bruno
                  Shubert, Associate Professor, Operations
                  Research

Sponsor: Foundation Research Program (6.1)

Objective: This study examines combinatorially the binary
                  trees which arise in many computer science
                  applications involving sorting, information
                  retrieval and other fundamental techniques.
                  The analysis is intended to provide information
                  necessary to analyze algorithms based on
                  manipulation of binary trees, thus providing
                  a method to estimate work factors, memory
                  region, and other characterizations of expense
                  and efficiency of computer programs.

Summary: A closed form counting formula for the number
                  of binary trees with n nodes and height
                  k was developed and restated as a recursion
                  more useful computationally. A generating
                  function for the number of nodes given height
                  was developed and used to find the asymptotic
                  distribution of binary trees. An asymptotic
                  probability distribution for height given
                  the number of nodes was derived for equally
                  likely binary trees. Random binary trees
                  (resulting from insertion sorting a random
                  string of key symbols) were counted in terms
                  of the mapping of permutations of n symbols
                  to binary trees of height k. An explicit
                  formula for this number was given with an
                  equivalent recursive definition for computational
                  use. A generating function was derived for
                  the number of symbols given height. Lower
                  and upper bounds on random binary tree height
                  were developed and shown to approach one
                  another asymptotically as a function of
                  n, providing a limiting expression for the
                  expected height. The random binary trees
                  were examined further to provide expressions
                  for the expectations of the number of vacancies

at each level, the distribution of vacancies
over all levels, the comparisons required
for insertion of a new random symbol, the
fraction of nodes occupied at a particular
level, the number of leaves, the number of
single vacancies at each level, and the number
of twin vacancies at each level. A random
process was defined for the number of symbols
required to grow a tree exceeding any given
height. Tabulations and figures were prepared
for all new results.

Publications: G. G. Brown and B. O. Shubert, "On Random
Binary Trees," <u>Technical Report</u>, NPS55Bw76061,
June 1976.

Title: On the Stability of Multidimensional Digital
                  Filters

Investigator: Associate Professor Daniel L. Davis, Mathematics
                  Department

Sponsor: Foundation Research Program (6.1)

Objective: To obtain necessary and/or sufficient conditions
                  for the stability of causal, recursive,
                  "all-pole" multidimensional digital filters
                  in terms of geometric inequalities between
                  the coefficients of the transfer function
                  which describes the filter.

Summary: Present methods for determining the stability
                  of a filter are iterative and consequently
                  it is difficult to determine the "cause"
                  of filter instability in terms of the transfer
                  function coefficients. In the present
                  research, a new approach to the problem
                  of filter stability has been developed
                  by means of which it is possible to determine
                  the precise inequalities which must hold
                  between coefficients in order to guarantee
                  stability. Such criteria are known for
                  one dimensional filters and are practically
                  essential in filter design. Although the
                  method of this research is not yet fully
                  developed, stability criteria for relatively
                  complicated multidimensional filters can
                  be derived as a result of its application.
                  Moreover, the approach is completely general,
                  irrespective of the order or dimension.

Publications: Daniel Davis and L. Souchon, "Stability
                  Conditions for N-Dimensional Digital Filters,"
                  IEEE Asilomar Conference, Nov. 1975.

Title: The Use of Time Series in Improving Meterological Forecasting

Investigators: Dean R. R. Fossum, Professors C. Comstock and F. D. Faulkner, Mathematics

Sponsor: Foundation Research Program (6.2)

Objective: To improve meteorological forecasting by the use of time series. Let us consider a typical meteorological variable such as the 500 mb height over the surface of the earth. It can be represented as finite Fourier series

$$\sum_{1}^{N} a_i \, Y_i(\phi,\theta)$$

in which ϕ is latitude, θ is longitude, and Y_i is a composite of Legendre functions in $\cos \phi$ and trigonometric functions of θ. The coefficients a at a time t define a time series $A_n = (a_{in})$. At each time t_n, new values are generated by integrating to get predictions

$$\hat{A}_{n,1}, \ \hat{A}_{n,2}, \ldots \hat{A}_{n,10},$$

say, for a 5-day forecast. In the interval t , t observations are made. The predicted values, the observations, and usually, an equation such as the balance equation, are combined to yield filtered or analyzed values $\hat{A}_{n+1}$. In this way a set of corrections to predicted values is generated.

It is the purpose of this study to analyze the set of corrections

$$z_n = \hat{A}_n - \hat{A}_{n-1,1}$$

as a time series to see if it shows trends that can be predicted to improve the forecasts. Initial work was done by Jones (1964). Since that time new techniques for integrating and for generating the Fourier series have been developed.

11

Preliminary programs have been generated
and it appears that the numerical programs
are almost ready. Jones suggested a stationary
(time invariant) time series. Initial analysis
of simulated data indicates that it is inadequate.
A program for a series of the ARIMA type,
(Auto Regressive Integrated Moving Average)
has been made up.
The principal problem envisioned is
to sort out the terms in Z_n that are significant,
to estimate those with a series of proper
low degree, and to adjust the various parameters
so as to effect a suitable compromise between
improvement and computational complexity.

Publications: None

12

Title: Analysis and Evaluation of Procedures for Computing Lower Bounds for System Reliability

Investigators: T. Jayachandran, Associate Professor of Mathematics, and A. L. Schoenstadt, Assistant Professor of Mathematics

Sponsor: Foundation Research Program (6.2)

Objective: Analyze competing procedures available for computing lower bounds on system reliability from individual component failure data. More specifically, for two of the most commonly cited, the statistically exact Lieberman-Ross (L-R) Method and the approximately optimal method of Mann and Grubbs (M-G), (a) Determine the effect in the L-R bound of a priori ordering the component failure data, (b) Determine a measure of the amount of data unused in calculating the bound, (c) Evaluate the accuracy of the M-G procedure, (d) Study the robustness of the L-R and M-G procedures when the exponential assumption is violated, i.e., for example when the failure times have Weibull distributions instead of exponential, and (e) Determine the accuracy of M-G bounds for parallel systems and other coherent systems with different types of data such as time to failure data or success-failure data.

Summary: The statistically exact L-R method suffers from two major drawbacks. First, the computed bounds can be altered by a permutation in the order in which the components failed, even though the absolute failure times are unchanged. Second, the procedure does not utilize all the component failure data which is available, i.e., some data is "lost." Both aspects of this method were investigated in some detail. Using analytic techniques, expressions were derived for the mean and variance of the L-R bounds as a function of sample size, thus yielding insights into the effect of data order permutation. Expressions were also derived for the expected

amount of "lost" data. Then, simulation
techniques were used to investigate the
effect of lost data, by simulating subsystem
failures, then a priori ordering the resulting
failures to make maximum use of the available
data. It was determined that this a priori
ordering did not improve the estimating
procedure.

Investigations into objectives (c) through
(e) is ongoing.

Publications: A. L. Schoenstadt, "The Influence of Data
Order on the Lierberman-Ross Method," NPS
Technical Report #NPS53Zh76047.

Title:	Numerical Solution of Very Large Sparse Systems of Stiff Ordinary Differential Equations
Investigator:	R. Franke, Associate Professor, Mathematics
Sponsor:	Foundation Research Program (6.1)
Objective:	The objective was to generate a computer code which could solve the very large, sparse, stiff, and implicit ordinary differential equations arising when the finite element method is used to discretize the space domain of time dependent partial differential equations. Sparse storage techniques for the matrices and an iterative linear equation solver were to be used to make efficient use of storage.
Summary:	An existing program, DFASUB, due to Brown and Gear (R. L. Brown and C. W. Gear, "Documentation for DFASUB - ...," Report No. UIUCDCS-R-73-575, University of Illinois at Urbana-Champaign, Urbana, Illinois, July 1973) was selected as being an appropriate starting point. DFASUB was modified to incorporate the objective ideas and to be more user oriented. Investigation of the linear system of equations for the quasi-Newton iterates in Gear's method revealed that iterative techniques should be very efficient for their solution. This was subsequently verified when test problems executed several times faster, using less storage, than programs previously used for this type of problem. The versatility of the program allows the user to easily incorporate standard elimination techniques for solution of linear systems when necessary. The program is available and being used for production computer runs.
Publications:	Richard Franke, "A Program for the Numerical Solution of Large Sparse Systems of Algebraic and Implicitly Defined Stiff Differential Equations," <u>Technical Report</u> #NPS53Fe76051, May 1976.

Title: Necessary Conditions for General Problems Involving Higher Derivative Bounded State Variables

Investigator: I. B. Russak, Associate Professor of Mathematics

Sponsor: Foundation Research Program (6.1)

Objective: To obtain necessary conditions for solution of a complex problem in optimal control involving constraints of the form $\psi(t,x)= 0$ in which the control effects the state x through a set of second order differential equations.

Summary: By using the techniques of the calculus of variations, a set of first order necessary conditions is obtained for the above problem. The distinctions are made clear between these results and those obtained for problems in which the control effects the state x through differential equations of order not higher than one. The problem considered includes many direct applications to current naval projects, such as, optimal guidance of missiles.

Publications: None

Title: Analysis of Reliability Estimating Methods

Investigator: A. L. Schoenstadt, Assistant Professor of Mathematics

Sponsor: Foundation Research Program (6.1)

Objective: Analyze certain properties of the Lieberman-Ross procedure for computing system reliability bounds from subsystem (component) failure data.

Summary: The Lieberman-Ross (LR) method is a statistically exact procedure for determining lower bounds on system reliability from subsystem (component) failure data. The procedure suffers, however, from two major drawbacks. First, the computed bounds can be altered by a permutation in the order in which the components failed, even though the absolute failure times are unchanged. Second, the procedure does not utilize all the component failure data which is available, i.e., some data is "lost." Both aspects of this method were investigated in some detail. Using analytic techniques, expressions were derived for the mean and variance of the LR bounds as a function of sample size, thus yielding insights into the effect of data order permutation. Then, simulation techniques were used to investigate the effect of lost data, by simulating subsystem failures, then a priori ordering the resulting failures to make maximum use of the available data. It was determined that this a priori ordering did not improve the   timating procedure.

Publications: A. L. Schoenstadt, "The Influence of Data Order on the Lieberman-Ross Method," NPS <u>Technical Report</u> NPS53Zh76047.

Title: Discrete Transforms and Convolutions

Investigator: Carroll O. Wilde, Professor, Department of Mathematics

Sponsor: Foundation Research Program (6.1)

Objective: Study the problem of finding the convolution operation that is appropriate for a given discrete transform, and the reverse problem of finding a transform for a given convolution.

Summary: Image science includes the total scenario of starting with a given object, forming an image of the object, transmitting the image from one location to another, detecting the transmitted image, processing the detected image, and displaying the processed image. Of primary concern for computer application is the case where the image is digitized, so that it can be represented as a discrete function over a set of lattice points, and discrete transforms and convolutions play a vital role in digital image science.

The overall objective has been approached by concentrating on one of the specific one-dimensional problems involved. Given a finite group $G = \{g_1, \ldots, g_n\}$, with g_1 the identity, we relabel the elements as $\{1, \ldots, n\}$. If x, y are n-dimensional column vectors, we define the convolution of x and y to be the vector x * y whose i^{th} component is

$$(x*y)_i = \sum_{j=1}^{n} x_{ij^{-1}} y_j \; .$$

The problem is to find a discrete transform, which is represented by a unitary matrix M whose columns form a representation of the original group, such that $M(x*y) = MxMy$. (The justaposition on the right denotes the linear product:

$$MxMy = \sum_{i,j} x_i y_i \; (\alpha_i \alpha_j),$$

18

where $\alpha, \ldots, \alpha_n$ are the columns of M.)
If we define the incidence matrices
$\Lambda_1, \ldots, \Lambda_n$ by

$$\Lambda_k = (\lambda^k_{ij})_{nxn}, \text{ where } \lambda^k_{ij} = \begin{cases} 1 & \text{if } i = kj \\ 0 & \text{if } i \neq kj \end{cases},$$

then convolution can be represented by

$$(x*y) = x^T \Lambda_i y .$$

With this notation, the above problem can
be reduced to that of solving a matrix equation
of the form

$$\sum_{i=1}^{n} t_i \Lambda_i = \begin{pmatrix} t_1^2 & t_1 t_2 \cdots t_1 t_n \\ t_2 t_1 & t_2^2 & \cdots t_2 t_n \\ t_n t_1 & t_n t_2 \cdots t_n^2 \end{pmatrix}$$

By equating columns, we can replace this
matrix equation by n eigenvalue problems
$A_i t = \lambda t$, where $t = (t_1, \ldots, t_n)^T$. Successful
solution of the n simultaneous eigenvalue
problems under the constraints noted above
would then yield the desired matrix M.

In addition to the above delineation
of the problem, results to date have included
solution of the problem for almost all groups
through order eight. Continuation of the
study is centering on efforts to find algorithms
so that the process can be extended to more
complicated groups.

In conjunction with the above efforts,
a continuing image science seminar has been
conducted through the research period.
The seminar has featured speakers from NPS,
Stanford University, Stanford Research Institute
and ESL, Inc., and NUC. Several colloquium
lectures were given during the 1976 fall quarter
at NPS, and a symposium was also held at NPS
during the same quarter. Longer range goals

19

include formation of a dedicated image science
research laboratory at NPS, and possibly
development of a new curricular program if
a need can be identified.

Publications: None

Title: Development of a Theoretical Framework and
a Methodology for Analyzing Stages in a Naval
Officer's Career

Investigator: C. B. Derr, Associate Professor, Administrative
Sciences Department

Sponsor: Foundation Research Program (6.1)

Objective: To develop a theory and method for studying
officer career patterns

Summary: A thorough review of the existing research
on career patterns lead to several hypotheses
about career stages of naval officers. Further
discussions with Professors Dalton and Thompson
at Brigham Young University and Drs. Roberts
and Wilcox at NPRDC served to clarify initial
formulations. Finally, in this exploratory
research, two classes of MN 3105 were surveyed.
Tentative conclusions were reached as follows:
  1. Stage theory is relevant but not
telling
  2. Various communities espouse different
values and attract persons with corresponding
values (e.g., technical values for NAVAIR,
managerial values for Surface Warfare, security
values for CEC and Supply).
  3. It is presumed that at the early
period of one's career one is pre-selected
for higher rank by the quality of the billet
he occupies,
  4. Many officers are second-career oriented
  5. In-depth interviews are preferred
for collecting such sensitive information.
  A new research proposal entitled, "Naval
Officer Career and Quality of Life Study:
Implications for Retention and Work Productivity,"
builds on this exploratory research and has
been submitted to the Office of Naval Research
and approved.

Publications: None

Title: Development of a Methodology for Analyzing
                  Data Describing Officer Billets

Investigators: R. S. Elster, Associate Professor, Administrative
                  Sciences Department, and R. R. Read, Professor,
                  Operations Research Department

Sponsor: Foundation Research Program (6.1)

Objective: To develop and exercise methodologies useful
                  in comparing and contrasting naval officer
                  billets using data from job task inventories.
                  In the long run it is hoped the results will
                  facilitate the description of billets and
                  help to identify educational requirements.

Summary: A job task inventory questionnaire was prepared
                  by modifying (and abbreviating) earlier work.
                  It was administered to 96 Navy officers (mostly
                  students at NPS) and subjected to the techniques
                  of factor analysis, multidimensional scaling,
                  hierarchial clustering, and K-means cluster
                  analysis. The last of these techniques emerged
                  as the most useful in terms of the stated
                  objectives. It appears that a few billet
                  clusters (three in our data) are quite stable
                  in that they are sharply delineated from
                  the others and their content can be described
                  by a few task items. The clusters of the
                  remainder billets are not as clearly defined
                  but can be separated in useful ways.
                      The follow on step is to enhance the
                  questionnaire so that greater separation
                  power is available in certain areas, and
                  to apply it to a larger and more representative
                  sample. Cross validation techniques should
                  be included.

Publications: None

Theses Directed:

                  J. Lemke, Major (Fed. German Air Force),
                  "Methodologies of Officer Billet Classification,"
                  Master's Thesis, 1976.

22

Title: A Taxonomy of Systems Acquisition

Investigator: C. K. Eoyang, Assistant Professor, Administrative Sciences Department

Sponsor: Foundation Research Program (6.1)

Objective: To identify basic characteristics of technical systems acquired by the military to understand the dynamics underlying the management of these systems.

Summary: The research in progress is scheduled to be completed by January 1977. To date, data for forty-eight weapon systems have been collected representing a variety of projects from the Army, Navy, and Air Force. They include aircraft, ships, missiles, and torpedoes. Statistical analyses are underway to determine the relative contribution of several variables to the total variance in cost, schedule, and performance. Preliminary results indicate that simplistic cause-effect relationships are not strongly supported by the data, although several findings suggest a few intrinsic system characteristics are significant.

Publications: None

Theses Directed:

LT D. D. Henry, "Performance Correlates of Weapon System Projects in the Military," Master's Thesis, December 1976.

Title: A Multiattribute Utility Approach to Measure
                Quality of Health Care

Investigator: W. C. Giauque, Assistant Professor, Administrative
                Sciences Department

Sponsor: Foundation Research Program (6.1)

Objective: To demonstrate the power of a relatively
                new analytic technique, multiattribute utility
                analysis, in determining medical standards
                despite the presence of uncertainty and of
                multiple, often conflicting, outcome criteria.

Summary: Lacking objective standards of what "good"
                medical care is, the assessment of quality
                becomes a matter largely of judgment. Insofar
                as judgments and opinions differ, quality
                becomes impossible to measure. Even in cases
                where medical opinion subsequently agrees
                on proper procedures, a quantitative measure
                of quality still does not exist, making rational
                cost/benefit analysis more difficult. The
                factors which make quality standards difficult
                to define in medicine are (1) uncertainty
                is nearly always a major factor, both in
                the diagnosis of the patient's condition
                and in assessing the outcome of any procedure,
                and (2) it is usually necessary to simultaneously
                consider multiple, often conflicting outcome
                criteria. These are precisely the types
                of problems that multidimensional utility
                theory is designed to handle. In addition,
                this theory can also yield a quantitative
                measure of "goodness" for any particular
                course of action one cares to analyze. In
                this research the potential use of this technique
                in quality determination was explored and
                developed. Two particular medical problems:
                treatment of suspected streptococcal sore
                throat and treatment of hypertension, were
                investigated, and preliminary quality standards
                developed.

Publications: W. C. Giauque, "A Multiattribute Approach
                to Measure Quality of Health Care," Technical
                Report NPS55Gi76031, March 1976.

24

Theses Directed:

R. E. Kapernick, "Medical Decision Analysis:
An Application in Hypertension," Master's
Thesis, March 1975.

Title: Evaluation of RDT&E Manpower Utilization
                Through Structural Variables: Phase I

Investigator: William J. Haga, Associate Professor, Adminis-
                trative Sciences Department

Sponsor: Foundation Research Program (6.2)

Objective: Explore the development of structural variables
                as a surrogate, indirect, nonreactive indicator
                of appropriate use of manpower in RDT&E,
                using the Percentile Role Differentiation
                Indicator (PRDI) as a theoretical template
                for identifying deviations from an expected
                degree of complexity for varying organization
                sizes.

Summary: Reductions of defense budgets in current
                dollars by Congress, and in real dollars
                by inflation, compel the Navy to reduce
                military and civilian manpower. RDT&E activi-
                ties are attractive cut-back targets for
                manpower specialists because of the impression
                that they are an area of defense support
                "tail" rather than combat "teeth." An intuitive
                approach to reducing RDT&E manpower would
                be an across-the-board percentage cut.
                Yet manpower specialists (DASD-M&RA and
                Navy OP-121) know this approach involves
                the unforeseen consequence of missing consider-
                able "tail" while knocking out some "teeth."
                    The original proposal was to explore
                a way to give manpower specialists some
                assistance in distinguishing "teeth" from
                "tail" in terms of labeling RDT&E subunits.
                Phase I involved six activities:
                    1. Reviews of prior DOD, GAO, OMB studies
                of RDT&E effectiveness and recommendation.
                This has been done.
                    2. Travel to BUPERS to explore the
                quality and availability of structural data
                from RDT&E units. The Foundation grant
                for Phase I did not include travel money.
                    3. Development of a structural data
                report format and reporting procedures.
                This has not been done.
                    4. Exploration of computer programs
                for storing and processing a proposed structural

data base. This has not been done.

　　5.　Consideration of four basic structural variables to be analyzed through the PRDI. This has not been done.

　　The Foundation Grant for Phase I was made in April 1975. At that time, I assumed that Louis Moore III would be employed as a consultant during the summer quarter of 1975 to complete (a) the programming of the PRDI for easy use through the input of formal organization structure data and (b) develop the PRDI algorithms under differing general assumptions about the character of organizations being analyzed. Moore was not engaged as a consultant because his contract was cancelled as a possible conflict of interest. Thusly, the PRDI was not consummated.

　　Travel to BUPERS was unnecessary in large part because of the discovery of Navy manpower report documents available from central sources at Norfolk and San Diego. The manning documents on a handful of Navy RDT&E organizations were acquired for use in devising "teeth" and "tail" coding methods and in developing the format of a structural data report. No objective means of making the crucial "teeth" or "tail" distinctions could be found in the reported data. The only resort was to make arbitrary coding decisions which was the very kind of decision the study aimed to prevent. Even organizing the data for simple statistical descriptions proved forbidding because of the need for considerable coding and keypunching labor.

Publications:　William J. Haga, "Probabilistic Base Generator for Role Differentiation in Formal Organizations," Journal of Mathematical Sociology, with Louis Moore III, in revision.

　　　　　　　William J. Haga, "Probabilistic Baseline Generator for Role Differentiation in Formal Organizations," Technical Report NPS53Ml76521, February 1975 (with Louis Moore III).

27

Theses Directed:

        LT Robert H. Spencer, USN, "Time Series Test
of a Harmonic Series Model of Organization
Differentiation," Master's Thesis, March
1975.

        LCDR Michael Tanner, USN, "Structural Evolution
of a Procurement Command," Master's Thesis,
March 1975.

        LT Steven R. Alexander, "Structural Evolution
of Naval Air Squadrons," Master's Thesis,
March 1975.

Title: Modeling a Defense Contractor

Investigator: Carl R. Jones, Associate Professor, Operations Research and Administrative Sciences Department

Sponsor: Foundation Research Program (6.1)

Objective: To refine a model of a representative defense contractor and characterize the contractor's responses to exogenous influences.

Summary: Based on an earlier development of a representative defense contractor model, the following refinements were studied: the inclusion of dividends as a corporate decision variable, the market structure of subcontractors, and the contractor expectations of future events. Each of these phenomena were modeled and included in the refined version of the representative defense contractor. In addition, effort was devoted to the characterization of the contractor's responses to exogenous influences. While complicated mathematical expressions are derived, simple sign (plus or minus) results were not obtained. Thus, the contractor's responses require quantitative (magnitude) information to obtain simple direction of change (plus or minus) results. This suggests the need for a somewhat more abstract model to provide insight into contractor behavior.

Publications: None.

**Theses
Directed:** W. C. Ridder and M. K. Heinz, "Structure, Conduct and Performance of the U.S. Aerospace Industry," Master's Thesis, March 1976.

Title: Determination of Maximal Flows in Nonplanar
Networks by Using Dual Graphs

Investigator: Alan W. McMasters, Associate Professor,
Administrative Sciences Department

Sponsor: Foundation Research Program (6.2)

Objective: To develop a "dual graph" algorithm for
determining the maximal flows in a nonplanar
flow network having finite capacities on
the arcs. This is a continuing project.

Summary: The introduction of pseudo nodes at intersection
points of the arcs of a two-dimensional
projection of a nonplanar flow network allows
a dual graph to be constructed. The solution
to the primal flow problem can then be obtained
by solving for the shortest route through
the dual graph subject to special constraints
associated with dual arcs circumscribing
each pseudo node. These constraints, although
simple in form, are extremely difficult
to combine with the shortest route algorithm
to obtain a solution to the dual. An algorithm
has been proposed which appears promising
and proof of its validity is currently being
sought.

Publications: None

Title: Pattern Analysis Applied to Retention Data: Comparison of PAIN and STRAIN

Investigator: R. A. Weitzman, Associate Professor, Administrative Sciences Department

Sponsor: Foundation Research Program (6.1)

Objective: To develop STRAIN, which estimates pattern scores, and compare it with PAIN (already developed), which calculates pattern scores directly.

Summary: A "pattern score" is a score assigned to an individual who has a specific pattern of responses to a set of binary items. The acronyms PAIN and STRAIN stand for Pattern Analysis Item Nominator and STRuctural Analysis Item Nominator, respectively. The method of estimation used by STRAIN is to set mth- (and perhaps lower)-order covariances $E(X_1-M_1)(X_2-M_2)\ldots(X_m-M_m)$ among the binary items equal to zero. Different from PAIN, STRAIN can obtain estimates of pattern scores for response patterns that no member of the estimation sample has. The results, obtained from retention data on Navy enlisted men, suggest that these estimates may be quite reliable. Further research is necessary, however, to strengthen this conclusion.

Publications: None

Title: Global Optimization of Nonlinear Programming
                Problems

Investigator: J. K. Hartman, Associate Professor, Operations
                Research Department

Sponsor: Foundation Research Program (6.1)

Objective: To continue investigation of a class of
                linear approximating problems for nonconvex
                nonlinear programs.

Summary: In previous work the "Grid Linearization"
                algorithm for nonlinear optimization was
                extended to apply to separable nonconvex
                nonlinear programming problems.
                    Current research has focused on the
                properties of the method when roundoff errors
                are present in the computations and has
                resulted in an approximate optimality theorem
                in these circumstances.
                    A related effort has formally extended
                the method to nonseparable nonconvex problems.
                Although the mathematics of the nonseparable
                case is straightforward, it is believed
                that the method would be very difficult
                to use computationally.

Publications: J. K. Hartman, "Extension of the Grid Lineariza-
                tion Algorithm for Convex Optimization to
                Nonconvex Nonlinear Programs," Technical
                Report NPS55Hh75071, July 1975.

                J. K. Hartman, "Epsilon Optimality for a
                Global Optimization Algorithm," Technical
                Report NPS55Hh75121, December 1975.

                J. K. Hartman, "A Branch & Bound Method
                for Nonseparable Nonconvex Optimization,"
                Technical Report NPS55Hh75102, October 1975.

Title: Ridge Regression

Investigator: H. J. Larson, Professor, Operations Research Department

Sponsor: Foundation Research Program (6.1)

Objective: To review the current literature and examine the distribution of the ridge regression estimator over repeated samples.

Summary: Ridge regression is a subjective biased estimation technique whidh seems to give more sensible numerical estimates of unknown regression parameters than does ordinary least squares, in certain circumstances. A study was made of the variations on ridge regression described in the literature, and their applications. Some properties of an iterative Bayesian ridge regression estimation technique were derived. Several procedures for getting the distribution of the ridge estimator, over repeated samples, were investigated. None of these leads to simple methods of comparing the classical properties of ordinary least squares estimators with those of ridge estimators.

Publications: None

Theses Directed:

E. B. Lewis, "An Investigation of the Probability Distribution of the Ridge Regression Estimator for Linear Models," Master's Thesis, March 1976.

Title: Analysis of Discrete Time Resource Allocation
                  Policies with Applications to Budgeting

Investigators: K. T. Marshall, Professor, and F. R. Richards,
                  Associate Professor, Operations Research
                  Department

Sponsor: Foundation Research Program (6.1)

Objective: To analyze the stochastic properties of
                  the sequence of deficits produced over time
                  with various budgeting policies which lead
                  to correlated supplies and demands. Such
                  policies are commonly observed in government
                  budgeting procedures.

Summary: A set of policies in which current and future
                  budgets are determined as convex linear
                  combinations of past demands was postulated,
                  and the properties of the resulting deficits
                  and surpluses were determined. The sequence
                  of deficits was shown to be related to the
                  sequence of waiting times in a single-channel
                  queue. However, the usual assumptions of
                  independence made for queueing systems are
                  unrealistic in the context of many resource
                  allocation problems. Our results show that
                  certain strongly correlated systems can
                  be analyzed. Our results have applications
                  in correlated queueing systems as well as
                  a wide variety of resource allocation problems.

Publications: K. T. Marshall and F. R. Richards, "Analysis
                  of Deficits in Discrete Time Resource Allocation
                  Problems with Correlated Supplies and Demands,"
                  Technical Report NPS55MtRh76051, May 1976.

Conference
Presentations: K. T. Marshall, "Analysis of Deficits and
                  Surpluses Under Various Budgeting Policies
                  with Relation to Queueing and Scheduling
                  Problems," presented to Operations Research
                  Seminar Series at Bell Telephone Laboratories,
                  Holmdel, New Jersey, March 1976.

Title:　　　Study of Variable-Coefficient Lanchester-
　　　　　　　Type Equations of Warfare

Investigator:　J. G. Taylor, Associate Professor, Operations
　　　　　　　Research Department

Sponsor:　　Foundation Research Program (6.1)

Objective:　To extend the state-of-the-art for developing
　　　　　　　and analyzing solutions to Lanchester-type
　　　　　　　equations of warfare in order to develop
　　　　　　　insights into the dynamics of combat (by
　　　　　　　explicitly showing the dependence of combatant
　　　　　　　force levels on the physical parameters of
　　　　　　　the combat attrition process and on initial
　　　　　　　conditions) and also in order to facilitate
　　　　　　　sensitivity and other parametric analyses.
　　　　　　　In particular, a specific objective is to
　　　　　　　develop techniques for predicting the outcome
　　　　　　　(e.g., force annihilation) in variable-coefficient
　　　　　　　Lanchester-type combat from initial conditions
　　　　　　　without explicitly solving the attrition
　　　　　　　equations.

Summary:　　A mathematical theory was developed for predict-
　　　　　　　ing force annihilation from initial conditions
　　　　　　　without having to explicitly compute force-
　　　　　　　level trajectories for Lanchester-type equations
　　　　　　　of modern warfare for combat between two
　　　　　　　homogeneous forces with temporal variations
　　　　　　　in fire effectivenesses. It was shown that
　　　　　　　prediction of force annihilation involves
　　　　　　　a single parity-condition parameter, which
　　　　　　　depends on only the model's attrition-rate
　　　　　　　coefficients. A canonical auxiliary parity-
　　　　　　　condition problem was introduced for determining
　　　　　　　this parity-condition parameter. Further
　　　　　　　research was performed on constructing the
　　　　　　　solution to variable-coefficient Lanchester-
　　　　　　　type equations of modern warfare from so-
　　　　　　　called hyperbolic-like general Lanchester
　　　　　　　functions. The force-annihilation results
　　　　　　　provided further information about the mathematical
　　　　　　　properties of these Lanchester functions.
　　　　　　　Important new results were obtained on how
　　　　　　　the parity-condition parameter depends on
　　　　　　　the intensity of combat and the relative
　　　　　　　fire effectiveness of the combatants. Approximate
　　　　　　　solutions were also examined, and new error
　　　　　　　bounds were developed for the Liouville-Green
　　　　　　　approximation to initial-value problems.

This research also developed new "simple" victory-prediction conditions for two Lanchester-type models, one linear and the other nonlinear, of combat between two homogeneous forces with superimposed effects of supporting weapons not subject to attrition. These simple victory-prediction conditions involve only the initial conditions of battle and certain assumptions about the nature of temporal variations in the attrition-rate coefficients. They were developed for fixed-force-ratio-breakpoint battles by studying the force-ratio equation for the linear combat model. The inadequacy of previous victory-prediction results was explained by examining (for the linear combat model without the supporting fires) new "exact" victory-prediction conditions, which show that even the range of possible battle outcomes may be significantly different for variable-coefficient and constant-coefficient models.

Previous results on the optimal allocation of military resources to battle and associated optimization theory were revised for publication. For example, the committing of forces to battle was examined as a mathematical programming problem. It was shown that one can determine whether or not it is "beneficial" for the victor to initially commit his entire force by considering the instantaneous force-change ratio for Lanchester-type combat equations.

Publications: J. G. Taylor and C. Comstock, "Force-Annihilation Conditions for Variable-Coefficient Lanchester-Type Equations of Modern Warfare, I: Mathematical Theory," Technical Report NPS55Tw76081, August 1976.

Conference Presentations:

G. G. Brown and J. G. Taylor, "An Examination of the Effects of the Criterion Functional on Optimal Fire-Support Policies," Operations Research Society of America and The Institute of Management Sciences (ORSA/TIMS) Joint National Meeting, Las Vegas, Nevada, November 1975.

G. G. Brown and J. G. Taylor, "Canonical
Methods in the Solution of Variable-Coefficient
Lanchester-Type Equations of Modern Warfare,"
ORSA/TIMS Joint National Meeting, Las Vegas,
Nevada, November 1975.

J. G. Taylor, "On the Relationship Between
the Force Ratio and the Instantaneous Casualty-
Exchange Ratio for Some Lanchester-Type Models
of Warfare," ORSA/TIMS Joint National Meeting,
Philadelphia, PA, April 1976.

Theses Directed:

J. Craig, "The Effect of Uncertainty on Lanchester-
Type Equations of Combat," Master's Thesis,
1975.

B. G. Baskerville, "The Significant Parameters
Affecting the Modeling of Target Acquisition
of Ground Combat Targets from Tactical Helicopters,"
Master's Thesis, 1976.

D. W. Brewer, "A Parametric Analysis of the
Dismounted Final Assault," Master's Thesis,
1976.

J. N. Carpenter, "A Numerical Evaluation
of the Liouville-Green Approximation of Variable-
Coefficient Lanchester-Type Equations of
Modern Warfare," Master's Thesis, 1976.

Y. Lee and Y. Pi, "The Estimation of Lanchester
Attrition-Rate Coefficients for an Aggregated
Combat Model," Master's Thesis, 1976.

R. A. Martray, "Development of an Aggregated
Lanchester-Type Combat Model for the Evaluation
of Air-War Allocation Strategies in a Theater
Sector," Master's Thesis, 1976.

Title: Measurement of Nuclear Giant Resonances
by High Energy Electron Scattering

Investigators: F. R. Buskirk, E. B. Dally, J. N. Dyer and
R. Pitthan, Professors, Physics and Chemistry
Department

Sponsor: Foundation Research Program (6.1)

Objective: To investigate the collective modes of oscilla-
tion (giant resonances) of medium and heavy
nuclei by means of inelastic electron scattering,
using the electron linear accelerator (Linac)
as the source of high energy electrons.
Specific objectives include: (a) more positive
identification of the monopole (breathing
mode) resonance; (b) a systematic investigation
of the isovector and isoscalar quadrupole
resonances for nuclei ranging in mass from
58 to 238; and, (c) identification of the
octupole mode.

Summary: The efforts have fallen into two broad categories,
(a) Giant Resonance Research, and (b) Improvements
in Spectrum Analysis.
    (a) Giant resonance measurements were
made in ^{89}Y at 90 MeV and scattering angles
of 75°, 90°, 105° and 120°. Nine resonances
were observed in a range of excitation energy
from 6 to 38 MeV, and the results are listed
in the thesis (9). One very important result
of this experiment concerns the width of
the isoscalar E2 resonance (14.86 MeV).
In an early (1972) electron scattering experiment
by the Sendai group (Japan) with the neighboring
nucleus ^{90}Zr, a very large width of 4.8
MeV was found. This result was not surprising
at the time, but subsequent experiments
with many other nuclei in the ensuing years
would make this result hard to understand.
Our results indicate that the broad resonance
actually consists of two resonances, M1
at 13.6 MeV and E2 at 14.9 MeV.

(b) The Radiation Tail refers to the
continuous spectrum of electrons which accompanies
inelastic electrons scattering, and in fact
accounts for 90% or more of the electrons
seen in a spectrum. To obtain a nuclear
spectrum the radiation tail must be subtracted
and knowledge of its energy dependence is
essential. In the present spectrum analysis
procedure, the observed spectrum is fit
to adjustable resonances and a constant
time the radiation tail function. The constant
would be 1.0 only if the radiation tail
function were known exactly, but the experimental
values of the constant ranging from 0.9
to 1.1 indicate that the function is known
more accurately than had been expected (2).
(c) Related research is described in
the report on the NSF project.

Publications: G. L. Moore, F. R. Buskirk, E. B. Dally,
J. N. Dyer, X. K. Maruyama and R. Pitthan;
"The Widths of the E2 (T = 0 and T = 1)
Giant Resonances in ^{165}Ho," _Zeit Schrift fur_
Naturforschung, 31a, 668 (1976).

R. Pitthan and F. Buskirk, "Fine Structure
and Resonant Structure in   ," _Bulletin_
of the _American_ _Physical_ _Society,_ 21, 516
(1976).

Theses Directed:
D. H. DuBois and G. M. Bates, "Electro-Excitation
of Giant Resonances in ^{60}Ni Between 5 and
30 MeV Excitation Energy," Master's Thesis,
June 1976.

J. O. Shannon and W. H. Smith, "Electro-
Excitation of Giant Resonances Between 6.1
and 38 MeV Excitation Energy in ^{89}Y," Master's
Thesis, June 1976.

E. F. Gordon, "An Investigation of the Natural
Line Shape of the Giant Dipole Resonance,"
Master's Thesis, 1975.

Title:	Laser Produced Plasmas

Investigators: A. W. Cooper and F. Schwirzke, Associate
Professors, Physics and Chemistry Department

Sponsor: Foundation Research Program (6.1)

Objective: In this continuing project the interaction
is investigated between intense laser pulses
and targets. The dynamics of the laser
produced plasma and self-generated magnetic
fields are studied.

Summary: In the interaction of high-power pulsed
laser radiation with a solid target, gas
breakdown and subsequent plasma formation
in the vicinity of the surface dominate
the later transfer of energy and momentum
to the solid. The interaction of 20-nsec
300-MW pulses of 1.06-μm laser radiation
with aluminum targets in vacuum has been
studied. The time history of the target
impulse has been measured with a Sandia
quartz gauge. A time sequence of plasma
density maps constructed from floating double-
probe data has been used with measured expansion
velocities to estimate the plasma momentum.
The results show that the stress wave is
predominantly produced by about 10% of the
evaporated target material which is ionized
and expands from the surface in the form
of a hot plasma during and shortly after
the laser pulse. Initial measurements were
also made of target impulse in layered materials
(solar cell models) in air and vacuum environ-
ment using 5-10 J 250 μsec pulses from a
CO_2 TEA laser.

Publications: A. W. M. Cooper, F. Schwirzke, and K. M.
Brooks, Sr., "Time Development and Symmetry
of a Laser-Produced Plasma Plume on a Plane
Target," Bulletin of American Physical Society,
20, 1266 (1975). Presented by A. W. Cooper
at the Annual Meeting of the Division of
Plasma Physics of the American Physical
Society, St. Petersburg, Florida, November
1975.

F. Schwirzke, A. W. M. Cooper and P. Krehl, "Correlated Measurements of Laser Induced Stress Waves and the Dynamics of the Laser Produced Plasma," Bulletin of the American Physical Society, 20, 1266 (1975). Presented by F. Schwirzke at the Annual Meeting of the Division of Plasma Physics of the American Physical Society, St. Petersburg, Florida, November 1975.

R. S. Case, Jr. and F. Schwirzke, "Background Gas Pressure Dependence and Spatial Variation of Spontaneously Generated Magnetic Fields in Laser-Produced Plasmas," Journal of Applied Physics 46, 1493 (1975).

P. Krehl, F. Schwirzke and A. W. Cooper, "Correlation of Stresswave Profiles and the Dynamics of the Plasma Produced by Laser Irradiation of Plane Solid Targets," Journal of Applied Physics, 46 4400 (1975).

Theses Directed:

Francis T. Williamson, "Laser Generated Magnetic Fields," Master's Thesis, June 1976. (Thesis Advisor: F. Schwirzke)

Daniel J. Callahan, "Laser Plasma Particle Velocities," Master's Thesis, June 1976. (Thesis Advisor: F. Schwirzke)

Sydney A. Shewchuk, "X-Ray Diagnostics of Laser-Produced Aluminum Plasmas," Master's Thesis, June 1976. (Thesis Advisor: A. W. Cooper)

John F. Jacobson, "Examination of Laser-Produced Pressure Pulses in a Gallium Arsenide Solar Cell," Master's Thesis, June 1976. (Thesis Advisor: A. W. Cooper)

41

Title: Computer Simulation of Sputtering III

Investigator: Don E. Harrison, Jr., Professor, Physics
                and Chemistry Department

Sponsor: Foundation Research Program (6.1)

Objective: To prepare for publication previous investigations
                of the formation of clusters of particles
                sputtered by atomic ions, and to pursue
                the investigation, by computer simulation,
                of the sputtering of a copper surface by
                diatomic molecular ions.

Summary: (1) The paper was prepared and has been
                published, see Publications below.
                (2) The main thrust of the molecular sputtering
                effort has been suspended while further
                details of the atomic sputtering process
                are examined. A careful examination of the
                sputtering ratio, atoms sputtered per incident
                ion, as a function of the ion mass indicates
                that the momentum transfer mechanisms are
                quite different for small and large mass
                ratios. There are now clear indications
                that a light bullet sputters atoms near
                the impact point while heavy ions produces
                a liquid droplike effect. For heavy ions
                the near atoms do not sputter, but a ring
                of atoms approximately 5 Å from the impact
                point do. This effect must be studied in
                greater detail. An immediate consequence
                is that computation will be more time consuming
                for heavy ions because the target microcrystallite
                must be larger. The project will continue
                in FY77.

Publications: Don E. Harrison, Jr. and C. D. Delaplain,
                "Computer Simulation of the Sputtering of
                Clusters," Journal of Applied Physics, 47,
                2252-59, (1976).

Title: Homogeneous Catalysis by Palladium Complexes

Investigator: R. A. Reinhardt, Professor, Physics and Chemistry Department

Sponsor: Foundation Research Program (6.1)

Objective: To study the kinetics of olefin oxidation by a series of palladium complexes. This is part of the continuing research into ligand substitution processes.

Summary: As a continuation of experiments begun previously, the rate of oxidation of trans-2-butene to 2-butanone by $PdBr_4^{2-}$ in acidic aqueous media is being studied. The use of gas chromatography to follow the reaction permits monitoring the actual concentrations of both reactant and product as functions of time. From data thus far obtained over a limited range of concentrations of acid and bromide, the reaction mechanism appears to be the same as that found in chloride solutions, with nearly the same value found for the formation constant of the precursor complex, but a rate of reaction of this precursor to product an order of magnitude less with bromide than with chloride.

Future plans: once the $PdBr_4^{2-}$ study is properly completed, we shall examine the reaction with other complexes, using the stopped-flow apparatus when appropriate for the more rapid processes, as is expected with the tetraaquo complex.

Conference Presentations: R. A. Reinhardt (presenter) and K. J. Graham, "Kinetics of Oxidation of Olefins by Palladium (II) Complexes." Paper presented to the 31st Meeting of the Northwest Region of the American Chemical Society, Reno, Nevada, 15 June 1976.

Publications: None

Title: Characteristics of Resistance Wires Used for Atmospheric Turbulence Measurements in the Marine Environment

Investigators: Gordon Schacher, Associate Professor, and C. W. Fairall, Assistant Professor, Physics and Chemistry Department

Sponsor: Foundation Research Program and Naval Air Systems Command

Objective: The purpose of this project is to determine the effect of marine aerosols on resistance wires which are used to measure fluctuations in wind speed and temperature. This is a continuing project.

Summary: Resistance wires are used as sensors to measure fluctuations in air temperature and wind speed. Such measurements are being made at NPS in the marine environment where the wires are impacted by marine aerosols, primarily saline droplets, resulting in sea salt encrustation. It is possible for thick layers of salt to change the calibration of the wires and measurements of the responses of wires that have been encrusted in the laboratory. The laboratory coatings are much thicker than that normally produced by sea spray in the field, and enabled a change in wire sensitivity to be measured. Both the dc and ac response of hot wires used for wind speed measurements have been investigated and it is found that naturally occurring levels of encrustation are rarely sufficient to significantly affect wire calibration, and that it is possible to easily test to determine if the wires are severely coated. Measurements on temperature wires are in progress and the effects of fog droplet impaction will be investigated in the future.

Publications: Gordon Schacher and C. W. Fairall, "Use of Resistance Wires for Atmospheric Turbulence Measurements in the Marine Environment," Review of Scientific Instruments, 47, No. 6, 703, 1976.

C. W. Fairall and Gordon Schacher, "Frequency
Response of Hot Wires Used for Atmospheric
Turbulence Measurements in the Marine Environment,"
Review of Scientific Instruments, 47, No.12,
0065, 1976.

Title: Computer-Aided Acoustic Imaging

Investigator: John P. Powers, Associate Professor of Electrical Engineering

Sponsor: Foundation Research Program (6.2)

Objective: This study investigates the feasibility of using a computer to obtain images of objects from the amplitude and phase of the diffraction pattern caused by ultrasound reflected from or transmitted by an object. The specific objective of this period of research was to investigate the implementation of the scalar diffraction integrals on the computer and to design an experimental arrangement to magnetically record the ultrasonic diffraction pattern over a plane. This is a continuing project.

Summary: The study of the implementation of the diffraction integrals compared the Fresnel integral representation and a spatial frequency domain approach. Both techniques use two dimensional Fast Fourier Transform (FFT) algorithims but differ in their geometry and in other respects. Based on the considerations that a computer aided imaging technique would require several evaluations of the integrals at arbitrary distances and that the spatial frequency approach is compatible with all frequency domain operations (e.g., Weiner filtering), it was concluded that the implementation in the spatial frequency domain was advantageous for use in imaging systems that might include an image processing capability. During the course of study computer programs for both diffraction integrals were written. As part of the experimental verification of the imaging technique a mechanical raster scanning system was designed to cover a flat planar area while electronically sampling both the phase and amplitude of the ultrasonic diffraction pattern of various objects in the laboratory environment. When assembled in the future this data acquisition system will provide experimental verification of the results obtained in previous studies from computer simulated objects.

Publications: J. P. Powers, "Computer Simulation of Scalar
Linear Acoustic Diffraction," *Acoustical Holography*,
Vol. 7, Lawrence Kessler, Ed., Plenum Press,
New York.

Title: Magnetic Background Noise Studies

Investigator: George L. Sackman, Associate Professor of
                Electrical Engineering

Sponsor: Foundation Research Program (6.2)

Objective: The long-term objective of this study is to
                characterize the spectral density, amplitude
                probability density, and spacial cross-correlation
                of magnetic background noise. The immediate
                objective is to establish a magnetometer data
                acquisition system capable of recording simultaneous
                measurements of total field, vector field,
                and field gradient at several locations in
                a form suitable for analysis by digital computer.
                These studies are part of a continuing program
                to agument Navy system R&D in magnetic detection
                and degaussing of submarines.

Summary: This study is in its initial phase and the
                major effort during the period covered by
                this report was devoted to re-establishing
                a magnetic observatory site, using the NPS
                Cesium magnetometer. A data acquisition system
                based on direct measurement of the Larmor
                period was developed which has a response
                time less than 2.5 milliseconds. However,
                noise introduced by the FM tape recording
                system limited resolution to 0.3 gamma. An
                improved system using digital tape recording
                is being developed.

Thesis Directed:

LT C. L. Xefteris, USN, "A Magnetometer Data
Acquisition System," Master of Science, June
1976.

Title: Application of Recursive Comb Filter to MTI Radar Signal Processing

Investigator: T. F. Tao, Associate Professor of Electrical Engineering

Sponsor: Foundation Research Program (6.2)

Objective: To investigate the feasibility of using recursive comb filter as the canceller of a MTI radar.

Summary: When a recursive filter uses delay devices of N delay stages, its frequency characteristics have a comb feature with a period of fs/N where fs = sampling frequency. By properly designing the feed forward and the feedback coefficients, the comb filter characteristics can be made to have high attenuations at a series of periodically spaced frequencies at d.c. and the multiples of fs/N and good transmission in between. If fs/N is matched to the pulse repetition frequency of a radar, this type of comb filter can be used as the canceller in a MTI radar. However, additional requirements must be met for bandwidth consideration. Altogether, three relations should be satisfied:

Canceller requirement $=$ fs/N = PRF

Bandwidth requirement $=$ $BW \geq \frac{1}{2\tau}$

Sampling frequency requirement = $fs \geq 2BW = \frac{1}{\tau}$

where τ = radar pulse width

BW = electronic bandwidth

Several canceller type of comb filters have been studied both experimentally and theoretically using two types of delay lines: 8 bits CCD and 96 bits CTD delay lines. However, their bandwidth is not adequate for real MTI radar applications. Instead, simulated MTI radar signals with less demanding bandwidth requirement were used to investigate the feasibility of using this type of comb filter as cancellers.

The result is encouraging and is reported
in the following paper. Further investigation
is being continued because a new CCD of better
bandwidth and long enough delay time recently
became available (although its dynamic range
is more limited).

Publications: T. F. Tao, V. Iamsaad, S. Holmes, B. Freund,
L. Saltre and T. Zimmermann, "Sampled Analog
CCD Recursive Comb Filter," Proceedings of
1975 International Charge Coupled Device Applica-
tions Conference, San Diego, CA, October 1975,
pp. 257-266.

Theses Directed:

L. T. Saetre, "Sampled Analog Recursive Comb
Filters and Their Application to MTI Radar,"
Master of Science, December 1975.

S. V. Holmes, "Theory of Operation and Applications
of Sampled Analog Devices in Recursive Comb
Filters," Ph.D. Thesis, June 1976.

50

Title: Tropical Wave Dynamics

Investigators: C. P. Chang, Assistant Professor of Meteorology
and R. T. Williams, Professor of Meteorology

Sponsor: Foundation Research Program (6.1)

Objective: To study the dynamics of large-scale wave
motions in the tropical troposphere and lower
stratosphere in terms of theortetical interpreta-
tion of their development, maintenance and
structure and the inter-relationship between
them.

Summary: Many aspects of tropical waves are included
in this study, but the present emphasis is
on the excitation mechanisms of the various
types of waves. The main results obtained
so far include: (1) selection of stratospheric
Kelvin waves can be explained by randomly-
distributed heat sources in the troposphere;
(2) wave-CISK (instability due to internally-
induced cumulus heating) would give rise to
very small growth rates and large vertical
wavelengths; (3) inclusion of viscous damping
comparable to that derived from observational
studies would alter the equatorial wave theory
greatly for slowly-moving waves, and can explain
the basic character of the tropospheric waves;
(4) first order effect of a mean flow with
varying barotropic instability depends on
the relative contributions of several advective
terms; and (5) CISK will not greatly alter
the barotropic instability selection mechanism.

Publications: C. P. Chang, "Vertical Structure of Tropical
Waves Maintained by Internally-Induced Cumulus
Heating," Journal of Atmospheric Sciences,
33 729-739, 1976.

C. P. Chang, "Forcing of Stratospheric Kelvin
Waves by Tropospheric Heat Sources," Journal
of Atmospheric Sciences, 33, 740-744, 1976.

C. P. Chang, "Comments on Instability Theory
of Large-Scale Disturbances in the Tropics,"
Journal of Atmospheric Sciences, 33, August
1976.

C. P. Chang and R. T. Williams, "Barotropic
Instability of a Spatially-Varying Mean Flow,"
presented at the Conference on Atmospheric
Waves and Stability, Seattle, March-April
1976. Abstract published in Bulletin of American
Meteorological Society 57, 1976.

C. P. Chang, "Viscous Internal Gravity Waves
and Low-Frequency Tropical Oscillations,"
presented at the Tenth Technical Conference
on Hurricanes and Tropical Meteorology, Charlottes-
ville, VA, July 1976. Abstract published
in Bulletin of American Meteorological Society,
57, 1976.

Title: Aircraft Structures Research: Composite Stress Concentrations

Investigator: M. H. Bank, Assistant Professor of Aeronautics

Sponsor: Foundation Research Program (6.2)

Objective: To determine the effect on the stress distribution in an advanced composite structure of a hole or thermally degraded region. Three immediate objectives are being pursued: (1) a one-parameter characterization of residual strength as a function of ballistic damage size is being attempted; (2) an investigation of the effects of low energy impact on composite plates is underway; and (3) a concurrent investigation of a liquid-crystal inspection technique for evaluation of the extent of damage supports both (1) and (2). This is a continuing program.

Summary: Improvements have been made in the composite materials fabrication laboratory, permitting manufacture of flat plate specimens as large as 24" x 36". A precision cut-off machine with a diamond wheel has been added to facilitate specimen preparation. The ballistic-impact and ball-drop devices are operational and producing data.

    A photoelastic investigation of stress concentrations around central holes in finite glass-epoxy composite plates under uniaxial tension demonstrated that the state of stress was not adequately described by theoretical solutions for homogeneous orthotropic plates. Stress concentration factors were shown to be dependent on hole size. Strain gage investigations of stress concentrations around off-center holes in similar plates under uniaxial load have shown that the effect of hole size on the stress concentration factor is increased when the hole is moved toward the unloaded edge.

    Ball-drop testing of graphite-epoxy panels is producing interesting results. Damage to the specimens has been detected at low energy levels well before any visible damage takes place at the surface. Growth of the

damaged area is monitored under successive
impacts until fracture occurs. The kinetic
energy of the impacter required to fail the
plate seems to be essentially constant.
An attempt to correlate the impact at fracture
with computer predictions utilizing a linear
finite-element method solution was unsuccessful;
deflections are large and a non-linear solution
is required.

Inspection of damaged areas using various
techniques has been investigated. The most
promising method seems to be the use of liquid
crystals to detect anomalies in the heat-
transmission properties of the material.
Deliberately introduced de-bonds between
laminae have been detected seven laminae
from the front surface of an eight-ply plate
(i.e., one lamina from the back side.) Heat
transfer properties of the composite material
are being studied, and devices are being
designed to turn this technique from a qualitative
to a quantitative inspection procedure.

Publications: None

Theses Directed:

Sakol Vudhivai, "Stress Concentration in
Glass-Epoxy Composite Plates," Master's Thesis,
December 1975.

T. J. Davis, "Ballistic Range Development,"
Master's Thesis, June 1976.

R. T. Schaum, "Development of a Non-Destructive
Inspection Technique for Advanced Composite
Materials Using Cholestric Liquid Crystals,"
Master's Thesis, September 1976.

Title:	Test Data Control and Analysis
Investigator:	R. P. Shreeve, Associate Professor of Aeronautics
Sponsor:	Foundation Research Council (6.1)
Objective:	To remotely control the acquisition of and to obtain on-line reduction of data from traversing probe systems.

Summary: A programmable data acquisition system was
              constructed using an inexpensive microprocessor.
              The system was programmed to drive a probe
              survey mechanism, to rotate and set a probe
              into the flow direction, and to scan, record
              and punch onto the paper tape up to 48 channels
              of data. A direct interface to a Hewlett-
              Packard Model HP 9830 calculator system will
              complete the system and allow immediate display
              of reduced data using an X-Y plotter.

Publications: None.

Thesis Directed:

              D. D. Patton, "Microprogrammable Data Acquisition
              and Probe Control System (MIDAS IV) with
              Application to Compressor Testing," Master's
              Thesis, March 1976.

Title: Flow in Highly Loaded Rotors

Investigator: R. P. Shreeve, Associate Professor of Aeronautics

Sponsor: Foundation Research Program (6.2)

Objective: To explore the application of stationary
                hot wire, hot film and semi-conductor probes
                to the determination of the flow relative
                to a highly loaded rotor.

Summary: The flow in the first rotor of an impulse
                fan should be periodic in a stationary frame
                (fixed probes), or steady with respect to
                the rotor itself. It is proposed to determine
                the flow at a point in the rotor frame by
                controlled digital sampling (using real-time
                instrumentation) at one sample per revolution.
                Trigger signals at 1 per revolution and 1
                per blade have been designed. Digital logic
                with phase-lock-loop circuitry enables samples
                to be taken at fixed peripheral locations
                in the rotor frame, at arbitrary speeds.
                A periodic flow generator was built to provide
                30,000 HZ signals typical of rotor exit flow
                conditions. Semi-conductor measurements
                of impact pressure were made using the generator.
                Experimentation with hot wire probes will
                begin when the trigger and delay circuits
                have been incorporated satisfactorily into
                the real-time digital data acquisition system.

Publications: None

Title: Mass, Salt and Heat Transports in the Atlantic Ocean During the IGY

Investigator: Glenn H. Jung, Professor of Oceanography

Sponsor: Foundation Research Program (6.1)

Objective: (1) Use computer program to calculate geostrophic currents and associated transport values through vertical crosssections across the Atlantic Ocean at 36, 32, 24, 16 and 8N latitude; eventually sections at 48N and at 8, 16, 24, and 32S will also be processed;
(2) Develop computer plot and analysis program for results display;
(3) Compare data when separated seasonally to describe seasonal variation.

Summary: Card decks punched for use on an earlier NPS computer were adapted to present computer program format; cards for observations between depths of 3000 meters and the ocean floor were punched and added, as well as title cards with basic information for each of the 267 stations (comprising 5942 observations of temperature and salinity versus depth). Sections were processed with at least three runs each to obtain adjustment of the level of no motion (LNM) so net mass and salt transport values across each section are approximately zero. The initial run LNM was a first guess; the second run attempted to overcompensate the net results of the first trial; and the final run LNM was based on careful comparisons between the first and second trials by which selection of the optimum LNM was made.
    The total observations for sections at 36, 32, 24, 16, and 8N have been processed in this manner. Also the earlier 40N results summarized by Greeson have been recalculated for use here. The net resulting heat transport values at 40 and 36N compare well with prior estimates interpolated from earlier data for nearby sections. From 32 through 16N the new calculations are significantly lower than prior estimates; this may be the result of

IGY sections combining sets of observations
taken during different years and seasons for
one latitude (as for 32N and 24-27N); at 16N
the heat transport value is very small and
poleward, taken during the same autumn season
as the bulk of the 24N observations; this
may be reflecting an actual anomalously low
heat transport during that particular season
and year. At 8N the net transport is equatorward
which has been checked as computationally
correct, but this change in direction remains
to be explained. Data at 8N are taken about
6 months prior to observations at 24 and 16N
and may be consistent with those low values
mentioned above. The level of no motion used
varies somewhat around the 1100-meter level
in the open ocean; it is clear through the
balancing process used for optimizing the
LNM that no significant departure from this
general value will permit the required balance
of mass and salt transport across each section.

A thesis student has begun work on summarizing
the mass transport calculations into an overall
three-dimensional circulation model of the
North Atlantic Ocean between 40 and 8N. Careful
comparison of these with earlier calculations
will be included, and comparison with available
actual mass transport and current observations.

Code 481 of ONR has approved a proposal
for continuation of this project during the
next academic year, when detailed summaries
of the salt and heat energy circulations of
the North Atlantic should be completed from
0 to 48N. Comparisons of these large-scale
transports with those effected by smaller-
scale eddies will be made; objectives (2)
and (3) will be done. Future proposed studies
beyond next year will continue this work into
the South Atlantic Ocean.

Publications: None

58

Title   Size and Number Distributions of Suspended
Particulates in the 1.5 to 35 Micron Range
in Central California Coastal Waters in Relation
to the Spacial and Temporal Variations of
Water Temperature and Density

Investigator: Stevens P. Tucker, Assistant Professor of
Oceanography

Sponsor: Foundation Research Program (6.1)

Summary: The geographical and seasonal distribution
with depth of 1 - 35 micron particles suspended
in sea water is investigated by means of
standard hydrographic techniques. The size
analyses are made with a 15-channel Coulter
counter and include data from four cruises
to the north and south of Monterey Bay, Califor-
nia. The size distributions are presented
as isometric drawings showing particle number
density vs. particle size as functions of
depth from the surface in the case of single
station data and of horizontal distance when
data are for a given depth along lines of
stations located at distances of 1, 2, 3,
5, 7, 10, 15, 20, 25, and 30 n mi from shore,
or in the case of Monterey Bay, separated
by a distance of 1.5 n mi. A paper for submission
to the Journal of the American Geophysical
Union and a longer technical report containing
all the oceanographic observations from the
four cruises will be completed by early January
1977.

Publications: None.

Title: Structure of the California Countercurrent

Investigator: J. B. Wickham, Associate Professor of Oceanography

Sponsor: Foundation Research Program (6.1)

Objective: To describe the structure and flow in the latitude of Monterey in the California Counter-current, including the delineation of mesoscale oceanographic features of the system in the vicinity of its boundary with the California Current.

Summary: The most interesting result, from preliminary analysis of new XBT data acquired from the National Marine Fisheries Service (NMFS), is that a cyclonic eddy delineated by direct current measurements in early August 1972 appears to have persisted to nearly the end of that month. Observations of intermediate times suggest variations in the eddy's form and weakening during that period. Information on such short time scales of features such as this are rare.

Additional analysis has been completed on the annual variation of the water masses in the countercurrent region. It indicates that the "southern water" characteristics, at least in the year 1972-1973, appear with greatest intensity in a narrow band within 20 km of the coast in the period August through December with an abrupt onset and cessation. The August arrival is consistent with the pattern observed in 1971-72 in the same region.

A filamental structure of this same type with a maximum near the shelf edge also appears in the geostrophic analysis of "southern water" flow in the Coronado trough (off San Diego), the data for this analysis having been collected by this reporter in August 1971. Current meter measurements off of Oregon and Washington also indicate a "shelf-edge" jet.

Data processing continues, particularly digitizing of STD analogue records obtained by NMFS. Their analysis is needed to confirm, by geostrophy, the preliminary conclusions about the persistence of the cyclonic eddy described above.

Thesis Directed:

C. S. Nelson, "Wind Stress and Wind Stress Curl Over the California Current," Master's Thesis, 1976.

61

Title: Dunkerley-Mikhlin Approximations for the Gravest
                  Frequency of a Vibrating System

Investigator: John E. Brock, Professor, Mechanical Engineering
                  Department

Sponsor: Foundation Research Program (6.2)

Objective: To sharpen and extend the method, usually
                  known as "Dunkerley's Method" employed for
                  obtaining a lower bound for the gravest frequency
                  of a simple vibrating sound.

Summary: A method has been developed for analyzing
                  discrete and/or continuous vibrating systems
                  so as to obtain approximations of various
                  degrees of accuracy for the gravest (nonzero)
                  frequency of vibration. The treatment of
                  cases involving rigid body modes is new, powerful,
                  and particularly interesting in that it involves
                  the compliance (flexibility) of a related
                  system in which the rigid body modes are arbitrarily
                  suppressed in an non-unique manner. Also
                  new is the ability to obtain higher order
                  approximations by iterating a certain matrix
                  (in the discrete case) or by iterating a Green's
                  function in the continuous case. The method
                  has been applied to a number of cases having
                  engineering significance. In particular some
                  remarkably accurate and simple formulas have
                  been developed for some useful cases of beam
                  vibration.

Publications: J. E. Brock, "Dunkerley-Mikhlin Estimates
                  of Gravest Frequency of a Vibrating System,"
                  Journal of Applied Mechanics, Vol. 43, Series
                  E, No. 2, June 1976 (Volume 98 of the Transactions
                  of the American Society of Mechanical Engineering),
                  345-348.

                  J. E. Brock, "Asymmetric Moment Loading of
                  Annular Elastic Plates," Journal of Applied
                  Mechanics, Vol. 43, Series E, No. 2, June
                  1976 (Volume 98 of the Transactions of the
                  American Society of Mechanical Engineers),
                  353-355.

                  J. E. Brock, "Dunkerley-Mikhlin Estimates
                  of Gravest Frequency of a Vibrating System,"
                  Technical Report NPS59Bc75101, October 1975.

J. E. Brock, "DM Approximations for the Gravest
Frequency of a Vibrating System," Technical
Report NPS59Bc75111, November 1975.

Conference Presentations:

J. E. Brock, "Dunkerley-Mikhlin Estimates
of Gravest Frequency of a Vibrating System,"
presented at the National Conference of Applied
Mechanics, University of Utah, Salt Lake City,
Utah, June 1976.

Title: Finite Element Formulation for Doubly Curved
Shells

Investigator: G. Cantin, Professor, Mechanical Engineering
Department

Sponsor: Foundation Research Program (6.2)

Objective: The objective of the project was to review
results obtained by G. Fonder of the University
of California at Berkeley, that contradicted
similar results obtained here at the Naval
Postgraduate School, by Dean Kiess, one of
our graduate students.

Summary: The results of Kiess were reproduced and found
to be seemingly correct. It was impossible
to reproduce the results of Fonder and there
are indications that his computations may
be erroneous. The work is not finished and
had to be abandoned for more urgent projects.
The support received from the Foundation was
returned to the Foundation.

Publications: None

Title:	Synthesis of Advanced Marine Vehicles
Investigator:	A. E. Fuhs, Professor of Mechanical Engineering
Sponsor:	Foundation Research Program (6.2)
Objective:	To develop a computer program which provides for computer-aided synthesis of an advanced marine vehicle.

Summary: A modern navy has a variety of marine vehicles from which to choose including hydrofoil craft, capture air bubble, surface effect ships, submerged hull, conventional hull, multiple hull, and wing-in-ground-effect. Each class of vehicle has different trade offs which can be demonstrated by a realistic computer-aided synthesis program. One of the vehicle classes will be chosen for emphasis.

To initiate the work on the subject of advanced marine vehicle synthesis, a series of lecturers were invited from NAVSEC, NAVSEA, industry and universities. These lectures established a benchmark on current state-of-the-art. As a result, the thrust of NPS effort becomes clear and duplication of work done elsewhere is avoided.

One project initiated as a result of a preliminary work is the evolution of a remotely controlled minesweeper. Professor Fuhs visited MINRON 12 in Charleston, SC to coordinate the work. MINRON 12 has a direct interest in the remotely controlled minesweeper. The project extends into FY7T and FY77.

Publications: None

Title: A Study of the Secondary Flow in a Curved
                  Rectangular Channel

Investigator: M. D. Kelleher, Associate Professor, Mechanical
                  Engineering Department

Objective: The objective of this work has been to study
                  the structure of the secondary motion induced
                  by centrifugal forces in a curved channel
                  of large aspect ratio. The study was carried
                  out using a hot wire anemometer system which
                  was capable of traversing in two directions
                  over the channel cross section.

Summary: The apparatus for the present study consists
                  of a plexiglas channel with a contraction
                  inlet followed by a straight section 122
                  cm. long. This is then followed by the curved
                  test section. The flow is maintained by
                  suction from a centrifugal blower. A rotometer
                  is installed between the outlet of the test
                  section and the blower. The flow cross section
                  is 0.635 cm by 25.4 cm for an aspect ratio
                  of 40. The straight section immediately
                  down stream of the inlet nozzle is of sufficient
                  length for the flow to be fully developed
                  before entering the curved section. With
                  the high aspect ratio of the flow cross section
                  the flow is essentially two dimensional Poiseuille
                  flow before entering the curved section.
                  The curved section of the channel turns through
                  180 degrees with the radius of curvature
                  of the outer (concave) wall being 30.48 cm
                  and the radius of the inner (convex) wall
                  being 29.84 cm. The hot wire anemometer
                  traverse is mounted through the convex wall
                  at a location 135 degrees downstream of the
                  start of the curved section.
                      This traverse mechanism is free to move
                  in both the spanwise direction and the radial
                  direction across the channel gap. The movement
                  in the spanwise direction is controlled by
                  a DC Stepper motor and sweep drive unit.
                  With this system the speed of traverse could

be controlled over a very wide range. For
these experiments the spanwise traverse was
run at a speed of 0.85 mm/sec. The output
from the sweep drive unit also served as
a linear displacement transducer which indicated
the spanwise position of the hot wire probe.
The movement in the radial direction is controlled
by a hand operated micrometer unit. Although
the traverse mechanism was capable of sweeping
15.24 cm in the spanwise direction, during
the actual measurements it was found that
a 5.0 cm traverse gave good results. With
the relatively slow traverse speed of 0.85
mm/sec. a single traverse required approximately
one minute.

The velocity surveys were made as follows:
the blower for the channel was set to provide
the desired flow rate. With the traverse
set at the initial spanwise position the
hot wire probe was set at the desired radial
position by means of the micrometer. After
the initial position of the hot wire probe
has been established the sweep drive mechanism
was turned on to begin the automatic traverse
of the hot wire across the channel. When
the 5 cm traverse was completed the traverse
was reversed to return the probe to its original
position. The radial position was then changed
by 0.635 mm by adjusting the micrometer setting
and a new traverse was begun. The procedure
was continued until the probe was at a position
0.635 mm from the concave wall. This was
the closest position for traversing the hot
wire probe. The data was recorded directly
on an x-y plotter. The output from the sweep
drive unit representing spanwise displacement
was recorded on the x axis and the linearized
signal from the hot wire probe representing
velocity was recorded on the y axis. The
velocity surveys were conducted for three
different flow rates corresponding to Dean
numbers of 79.?, 94.9, and 113.5. In each
of these cases spanwise velocity traverses
were made at six different radial positions.
The periodic nature of the secondary flow
is clearly illustrated. As would be expected
the amplitude of the periodic motion is greatest
in the region close to the concave wall.
It is interesting to note that the velocity

profile on the convex side of the mid-plane
is 180 out of phase with the velocity profile
on the concave side of the mid-plane. This
is similar to the phenomenon observed by
Shubaur and Skramstad in their measurement
of the Tollmien-Schlichting waves in the
boundary layer on a flat plate. In the sense
that the mid-plane is the location across
which the phase reversal takes place, it
is similar to the critical layer for Tollmien-
Schlichting waves. The phase shift is present
at all three Dean Numbers. Average values
of the wave number were calculated from the
velocity profiles for the three Dean Numbers.

Publications: None

Title: Transient Response of Submerged Structures Subjected to Blast Loading

Investigator: R. E. Newton, Professor, Mechanical Engineering Department

Sponsor: Foundation Research Program (6.2)

Objective: To demonstrate the capabilities and limitations of the finite element method (FEM) in studying the transient response of submerged structures subjected to blast loading. This is a continuing project.

Summary: The first phase of this investigation was reported by D. L. Atchison in his thesis. He showed that the problem could be separated into a study of the propagation of a blast wave past a fixed rigid obstacle and a study of the motion of a submerged structure under loadings found in the propagation study. He also demonstrated that FEM gives satisfactory results for the two-dimensional problem of the propagation of a plane-fronted acoustic blast wave past a circular cylinder with axis parallel to the wave front.

The current phase of the investigation has dealt with the corresponding response motion of an infinitely long, ring-stiffened elastic cylinder having uniformly spaced elastic bulkheads. This problem is resolved into two-dimensional sub-problems by using Fourier series representation of the circumferential variation of fluid pressure and structural displacement. FEM solutions of the sub-problems are superposed to find resulting deflections and stresses. The critical combinations of blast pressure and submergence pressure, just sufficient to produce shell collapse, have been determined.

Publications: R. E. Newton and D. L. Atchison, "Response of a Ring-Stiffened Cylinder to an Acoustic Blast Wave," Proceedings of the Second International Symposium on Finite Element Methods in Flow Problems, Santa Margherita, Italy, June 1976.

Theses Directed:

> D. L. Atchison, "Finite Element Solution of
> the Interaction of a Plane Acoustic Blast
> Wave and a Cylindric Structure," Master's
> Thesis, June 1974.

Title: Nuclear Reactor Dynamics With Temperature Dependent Feedbacks

Investigator: D. H. Nguyen, Associate Professor, Mechanical Engineering Department

Sponsor: Foundation Research Program (6.1)

Objective: To obtain solutions of Nonlinear Space-Time Reactor Dynamics Problems

Summary: The explicit inclusion of temperature dependent feedbacks results in nonlinear neutron transport problems. The one-velocity, space-time dependent diffusion equation has been solved, using the finite element method, for the multiregion reactor system under highly discontinuous initial disturbances. The space dependence of fast reactor dynamics under such conditions has been examined.

The multi-group space-time dynamics problem has also been solved under uniform initial disturbances. The method used is the Newton-Raphson-Kantorovich iterative technique applicable to operator equations. The space discretization is achieved by finite element method, and the resulting set of stiff ODE is integrated by a modified Gear's method. The results show a very fast rate of convergence. The cost in terms of computer time and storage is well within reasonable limits, so that the method is attractive for the analysis of real systems.

Publications: Dong H. Nguyen, "Finite Element Solutions of Space-Time Nonlinear Reactor Dynamics," Nuclear Science and Engineering, 60, pp. 120-130, (1976).

Dong H. Nguyen, "Space-Time Solutions of Multigroup Nonlinear Reactor Dynamics Equations," Transactions of the American Nuclear Society, 23, p. 590, (1976).

Conference Presentations:

Dong H. Nguyen, paper presented at the 1976 Joint Meeting of the American and Canadian Nuclear Societies, Toronto, Canada. (June, 1976).

Title: Corrosion Studies on Zinc Anode Materials

Investigator: J. Perkins, Associate Professor of Mechanical Engineering

Sponsor: Foundation Research Program (6.2)

Objective: To determine the environmental and materials-related electro-chemical factors which determine corrosion film structure and morphology and corrosion kinetics for zinc anodes in sea water. The study is intended to shed light on the common problem of passivation of sacrificial zinc anodes, which renders them useless in their role as protection for structures such as ships' hulls and ocean platforms.

Summary: Scanning electron microscopy has been used extensively in the study of the morphology of anodic corrosion products formed under controlled electrochemical conditions in sea water electrolyte. Interest in this area is stimulated by the common naval use of zinc alloys as sacrificial galvanic anodes for cathodic protection of ship hulls. A common problem associated with this usage has been the development of apparent anode passivity, and therefore loss of protection due to current blockage. The Naval Postgraduate School (NPS) program was initiated with the aim of delineating the electrochemical and metallurgical features that are critical in this regard. Direct observation techniques have proved to be fruitful in following the mechanism of film formation. The general film structure consists of an array of zinc oxide (ZnO) crystallites nucleated with a population density on the order of 10^6 plates/cm^2. This represents a macroscopically porous and nonpassive film condition for the zinc anode. The crystallography growth mechanism, and kinetics of development of such films is being studied in detail utilizing microscopy, x-ray diffraction, and energy-dispersive x-ray analysis. Laboratory experiments are being conducted to delineate critical ranges of various electrochemical variables, including current density and velocity effects.

Publications: R. A. Bornholdt and Jeff Perkins, "SEM Examination of Corrosion Product Morphology for Anodically Polarized Zinc," <u>Metallography</u>, <u>8</u> (1975) 401-409.

J. Perkins and R. A. Bornholdt, "Corrosion Product Morphology in Anodic Electrocrystallization of Zinc Oxide on Zinc in Sea Water," <u>Corrosion Science</u> (in press).

J. M. Todd and J. Perkins, "Corrosion of Zinc Anodes in Sea Water," <u>Naval Engineers Journal</u> (in press).

J. M. Todd and J. Perkins, "Nucleation and Growth of Anodic Electrocrystallization Products on Zinc in Sea Water," <u>Corrosion</u>, (in press).

J. Perkins, "Growth of ZnO Crystals During Anodic Electrocrystallization," <u>Journal of Crystal Growth</u> (in press).

J. Perkins, W. H. Luebke, and J. M. Todd, "Anodic Corrosion of Zinc Alloys in Saltwater," TMS-AIME Fall Meeting 1976, Niagara Falls, NY, Sept. 20-23, 1976.

Theses Directed:

J. M. Todd, "Nucleation and Growth of Anodic Electrocrystallizied Products on Ship Hull Zinc in Saltwater Solutions," Mechanical Engineer Thesis, December 1975.

J. M. Price, "A Potentiokinetic Determination of Corrosion Rules in Artificial Seawater-Hypochloride Solutions," Master's Thesis, June 1976.

W. H. Luebke, "A Scanning Electron Microscope Study of the Effects of Anode Velocity and Current Density on the Corrosion of Ship Hull Zinc in Synthetic Seawater," Master of Science Thesis, June 1976.

73

Summary Title	Investigator	Type Funding
COMPUTER SCIENCE		
Large Scale Network Optimization	G. Brown	6.1
Analysis of Binary Trees Arising from Applications in Sorting and Information Retrieval	G. Brown	6.1
MATHEMATICS		
On the Stability of Multidimensional Digital Filters	D. L. Davis	6.1
The Use of Time Series in Improving Meterological Forecasting	R. R. Fossum C. Comstock F. D. Faulkner	6.1
Analysis and Evaluation of Procedures for Computing Lower Bounds for System Reliability	T. Jayachandran	6.1
Numerical Solution of Very Large Sparse Systems of Stiff Ordinary Differential Equations	R. Ranke	6.1
Necessary Conditions for General Problems Involving Higher Derivative Bounded State Variables	I. B. Russak	6.1
Analysis of Reliability Estimating Methods	A. L. Schoenstadt	6.1
Discrete Transforms and Convolutions	C. O. Wilde	6.1
ADMINISTRATIVE SCIENCE		
Development of a Theoretical Framework and a Methodology for Analyzing Stages in a Naval Officer's Career	C. B. Derr	6.1

Summary Title	Investigator	Type Funding
ADMINISTRATIVE SCIENCE, cont.		
Development of a Methodology for Analyzing Data Describing Officer Billets	R. S. Elster	6.1
A Taxonomy of Systems Acquisition	C. K. Eoyang	6.1
A Multiattribute Utility Approach to Measure Quality of Health Care	W. C. Giauque	6.1
Evaluation of RDT&E Manpower Utilization Through Structural Variables: Phase I	W. J. Haga	6.2
Modeling a Defense Contractor	C. R. Jones	6.1
Determination of Maximal Flows in Nonplanar Networks by Using Dual Graphs	A. W. McMasters	6.1
Pattern Analysis Applied to Retention Data: Comparison of PAIN and STRAIN	R. A. Weitzman	6.1
OPERATIONS RESEARCH		
Global Optimization of Non-linear Programming Problems	J. K. Hartman	6.1
Ridge Regression	H. J. Larson	6.1
Analysis of Discrete Time Resource Allocation Policies with Applications to Budgeting	K. T. Marshall F. R. Richards	6.1
Study of Variable-Coefficient Lanchester-Type Equations of Warfare	J. G. Taylor	6.1
PHYSICS AND CHEMISTRY		
Measurement of Nuclear Giant Resonances by High Energy Electron Scattering	F. R. Buskirk E. B. Dally J. N. Dyer R. Pitthan	6.1

Summary Title	Investigator	Type Funding
PHYSICS AND CHEMISTRY, cont.		
Laser Produced Plasmas	A. W. Cooper F. Schwirzke	6.1
Computer Simulation of Sputtering III	D. E. Harrison, Jr.	6.1
Homogeneous Catalysis by Palladium Complexes	R. A. Reinhardt	6.1
Characteristics of Resistance Wires Used for Atmospheric Turbulence Measurements in the Marine Environment	G. Schacher C. W. Fairall	6.1
ELECTRICAL ENGINEERING		
Computer-Aided Acoustic Imaging	J. P. Powers	6.2
Magnetic Background Noise Studies	G. L. Sackman	6.2
Application of Recursive Comb Filter to MTI Radar Signal Processing	T. F. Tao	6.2
METEOROLOGY		
Tropical Wave Dynamics	C. P. Chang R. T. Williams	6.1
AERONAUTICS		
Aircraft Structures Research: Composite Stress Concentrations	M. H. Bank	6.2
Test Data Control & Analysis	R. P. Shreeve	6.1
Flow in Highly Loaded Rotors	R. P. Shreeve	6.2
OCEANOGRAPHY		
Mass, Salt and Heat Transports in the Atlantic Ocean During the IGY	G. H. Jung	6.1

76

Summary Title	Investigator	Type Funding
OCEANOGRAPHY, cont.		
Size and Number Distributions of Suspended Particulates in the 1.5 to 35 Micron Range in Central California Coastal Waters in Relation to the Spacial and Temporal Variations of Water Temperature & Density	S. P. Tucker	6.1
Structure of California Countercurrent	J. B. Wickham	6.1
MECHANICAL ENGINEERING		
Dunkerley-Mikhlin Approximations for the Gravest Frequency of a Vibrating System	J. E. Brock	6.2
Finite Element Formulation for Doubly Curved Shells	G. Cantin	6.2
Synthesis of Advanced Marine Vehicles	A. E. Fuhs	6.2
A Study of the Secondary Flow in a Curved Rectangular Channel	M. D. Kelleher	6.2
Transient Response of Submerged Structures Subjected to Blast Loading	R. E. Newton	6.2
Nuclear Reactor Dynamics With Temperature Dependent Feedbacks	D. H. Nguyen	6.1
Corrosion Studies on Zinc Anode Materials	J. Perkins	6.2

PROGRAM REVIEW

The Foundation Research Program is monitored by the Pasadena Branch Office of the Office of Naval Research.

DISTRIBUTION LIST

Chief of Naval Research
Arlington, Virginia 22217

Code 100	1
Code 101	1
Code 102	1
Code 402	1
Code 400R	1

Deputy Chief of Naval Material (Development)
Navy Department
Washington, D. C. 20360

Code NAVMAT 03	1
Code NAVMAT 03B	1

Director of Laboratory Programs
Washington, D. C. 20360

Code NAVMAT 035	1
Code NAVMAT 035B	1

Office of Naval Research   2
Pasadena Branch Office
1030 East Green Street
Pasadena, CA 91106

Defense Documentation Center   2
Cameron Station
Alexandria, VA 22217

Library   2
Code 0142
Naval Postgraduate School
Monterey, CA 93940

Dean of Research   50
Code 012
Naval Postgraduate School
Monterey, CA 93940